

34

Professional Ratcheting Torque Wrenches

High Accuracy Torque Wrench with unmatched safety & accuracy

48 teeth Ratchet allows for an engagement angle of 7-1/2° which is ideal; providing both precise adjustment & non slip use

Chrome-Molybdenum alloy Steel Square Drive

To set required torque a. press safety button & pull out adjustment ring

- b. Turn ring to the desired value
- c. Press the safety button again & push back adjustment ring
- d. Wrench is set at desired torque & ready for use

Fully secure locking mechanism avoids accidental/forced adjustment To tighten fasteners, move Torque Wrench in clockwise direction. Reversing the ratchet allows the wrench to be used in anti-clockwise direction, used for loosening nuts & fasteners

Clearly audible click sound on reaching the required

Lightweight with a comfort grip handle & lens for clear reading of the set value

Accurate to ± 4% of reading

Each unit is individually serial numbered & includes calibration certificate traceable to International Standards Institute

Fully serviceable, repair kits available as spare

Ft-Ib models can be custom manufactured





Ratchet Lever Cr V Body (Mat Satin Finish) Dual Scale: Nm / Ft Lb. Lens 變 (Screen) Safety Button

Adjustment Ring

Fixed Head

SPARE PARTS & KITS

CAT NR.	DESCRIPTION	BOX QTY.	
RPR/TQW/NM/3-8A	Ratchet Kit for TQW/RT/3-8/50	1	
RPR/TQW/NM/1-2	Ratchet Kit for TQW/RT/1-2/100	1	
RPR/TQW/NM/1-2A	Ratchet Kit for TQW/RT/1-2/200	1	
RPR/TQW/NM/1-2B	Ratchet Kit for TQW/RT/1-2/340	1	
RPR/TQW/NM/3-4A	Ratchet Kit for TQW/RT/3-4/750	1	
RPR/TQW/NM/0-1A	Ratchet Kit for TQW/RT/0-1/1000	1	
RPR/TQW/GRP	Ratchet Handle	1	
PCAGE/RTW/1-2/3-8/STD	Planet Cage	1	

TQW/RT















ORDERING INFORMATION

CAT NR.	SQUARE DRIVE (INCH)	TORQUE RANGE (NM)	FINE SCALE (NM)	OVERALL LENGTH		NET WT.	BOX QTY.	
				(INCH)	(MM)	(KGS)		
TQW/RT/3-8/25	3/8	5-25	0.1	12.7	323	0.765	1	
TQW/RT/3-8/50	3/8	10-50	0.5	15.7	400	0.983	1	
TQW/RT/1-2/100	1/2	20-100	0.5	15.7	400	0.998	1	
TQW/RT/1-2/200	1/2	40-200	0.5	20.4	517	1.36	1	
TQW/RT/1-2/340	1/2	60-340	1	24.4	620	1.73	1	
TQW/RT/3-4/750	3/4	150-750	2.5	47.6	1210	5.85	1	
TQW/RT/0-1/1000	1	200-1000	2.5	59.0	1500	7.43	1	
D10	Torque wrench merchandiser stand (Torque wrench not included)							