

36 Aluminium Torque Wrenches

TQW/AL



NEW!

World's lightest precision torque wrench with unmatched features

50% Lighter

Lightweight yet robust aluminium construction makes this range of torque wrenches at least 50% lighter than corresponding steel models.



Perfect ergonomics & lightweight body makes these ideal for fatigue free usage in heavy workshop applications

Complete with extension bar for added leverage

Torque Indication

Progressive torque building upto the pre-set value easily detected by an audible sound & impulse

Sturdy Storage

Supplied in rugged blow moulded case for extra care and protection for your valuable tool



Integrated 3 Lever Chain Mechanism
Length independence, high accuracy and reliability every time over time



Length Independent
Irrespective of where the force is applied, whether in the middle of the handle or elsewhere, with both hands or with an extension tube, the torque value is always within an accuracy of $\pm 3\%$



Dual Scale Window
Clear window for reading in NM and lbf-ft*



Torque Adjustment
Secure push-pull knob with integrated hex key for easy setting of torque

ACCURACY

$\pm 3\%$

CONFORMS TO

DIN 6789
ASME B107.300-2010

IMPULSE - SOUND TORQUE INDICATIONS



Chrome Molybdenum
Square Drive: for higher strength and durability



Added Leverage
Supplied with an aluminium tube extension for increased leverage while tightening at high torque values

ORDERING INFORMATION

| CAT NR. | SG DRIVE | TORQUE RANGE | | GRADUATION | OVERALL LENGTH | | NET WT. (KG) | BOX QTY. |
|-----------------|----------|--------------|---------|------------|----------------|------|--------------|----------|
| | (INCH) | (NM) | (FT-LB) | | (INCH) | (MM) | | |
| TQW/AL/3-4/760 | 3/4 | 140-760 | 100-560 | 10 | 32-1/2 | 827 | 3.0 | 1 |
| TQW/AL/0-1/2000 | 1 | 750-2000 | N/A | 50 | 93 | 2370 | 11.7 | 1 |

*Only on 3/4". On 1" single window with reading in N-m only