

Manufactured to the highest level of DIN ISO 6789 & ASME B107.14M.-2004

Accurate to  $\pm 4\%$  of reading

Solid steel construction for enhanced durability

**Clearly Audible**

Click sound on reaching the required torque

Scale reading made easy with four torque readings engraved on the steel body

**Reversible Square Drive**

Direction of use can be changed/reversed by pushing the square drive to the opposite side

Convenient retracting lever provides quick and easy torque adjustment

Anti-slip grip provides comfort during continuous use

Comes with calibration certificate in a safe to store & carry blow moulded case

**NEW!**



**ACCURACY**

**$\pm 4\%$**

**CONFORMS TO**

**DIN 6789**  
**ASME B107.300-2010**

**IMPULSE - SOUND TORQUE INDICATIONS**

**ORDERING INFORMATION**

CAT NR.	SQUARE DRIVE	TORQUE RANGE		OVERALL LENGTH		NET WT. (KG)	BOX QTY.
	(INCH)	(NM)	(FT-LB)	(INCH)	(MM)		
TQW/CL/3-8/33	3/8	5-33	4-24	16-5/8	422	0.720	1
TQW/CL/3-8/68	3/8	12-68	10-50	18-23/32	476	1.05	1
TQW/CL/1-2/135	1/2	25-135	20-100	21-1/2	546	1.60	1
TQW/CL/1-2/225	1/2	50-225	40-160	23-1/2	597	2.30	1
TQW/CL/1-2/330	1/2	70-330	50-250	32-1/2	825	2.60	1
TQW/CL/3-4/800	3/4	200-800	140-600	42-1/8	1070	7.58	1
TQW/CL/0-1/1000	1	200-1000	140-740	55	1400	12.80	1

