

103

Digital Indicators

DGI

A very versatile range of digital indicators available in two levels of precision – Standard & High Accuracy

Robust construction

Suitable for both inch & metric measurements

Useful for absolute & tolerance measurement which allows for measure of upper & lower tolerances

Supplied with flat & lug back

Comes complete with CR 2032:3V battery

ORDERING INFORMATION

CAT NR.	RANGE			URACY	RESC	вох	
	(MM)	(INCH)	(MM)	(INCH)	(MM)	(INCH)	QTY.
STANDA	ARD						
DGI/1	0 - 12.70	0 - 1/2	± 0.02	± 0.0008	0.01	0.0005	5
HIGH AC	CCURACY						
DGI/2	0 - 12.70	0 - 1/2	± 0.005	± 0.0002	0.001	0.00005	5



4

Dial Indicators

DLG

Robust construction, mechanical dial indicator with bottom plunger


Furnished with lug-on centre back

Each revolution is indicated by a revolution counter

8 mm stem diameter for metric models and 3/8" for inch sizes

Available in inch & metric models

Meets AGD specifications





ORDERING INFORMATION

CAT NR.	RANGE	RANGE PER REVOLUTION	ACCURACY	RESOLUTION	DIAL READING	AGD	D	Н	BOX QTY.
DLG/5	0 - 5 mm	0.50 mm	± 0.03 mm	0.01 mm	0-50	1	42.00 mm	79.00 mm	5
DLG/10	0 - 10 mm	1.00 mm	± 0.03 mm	0.01 mm	0-100	2	58.00 mm	110.00 mm	5
DLG/1-2	0 - 1/2"	0.10"	± 0.002"	0.001"	0-100	2	2.28"	4.19"	5
DLG/0-1	0 - 1"	0.10"	± 0.002"	0.001"	0-100	2	2.28"	4.67"	5