

112

## **Magnetic Bases**

MB

Rigid & robust magnetic bases with vee grooves that securely fasten onto round ferrous jobs or machine tables

Equipped with convenient ON/OFF control switch

Three precision ground magnetic surfaces allow these to be used horizontally, vertically or even upside down

Available in two versions: a. Articulating Arm Type 3 articulating joints lockable using a single

knob. Suitable for 3/8" & 8 mm stems & test indicators with dovetail clamping mechanism b. Fixed Arm Type

Threaded M8 × 1.25





## ORDERING INFORMATION

| CAT<br>NR.  | BASE DIMENSION (L × W × H) |                         | ARM LENGTH |        | MAGNETIC PULL | вох  |
|-------------|----------------------------|-------------------------|------------|--------|---------------|------|
|             | (MM)                       | (INCH)                  | (MM)       | (INCH) | (KG)          | QTY. |
| ARTICULAT   | ING ARM TYPE               | 1                       | 1          | 1      |               |      |
| MB/30       | 30 × 40 × 35               | 1-3/16 × 1-9/16 × 1-3/8 | 180        | 7-3/32 | 30            | 1    |
| MB/80       | 50 × 60 × 55               | 2 × 2-3/8 × 2-3/16      | 280        | 11     | 80            | 1    |
| MB/80L      | 50 × 60 × 55               | 2 × 2-3/8 × 2-3/16      | 340        | 13-3/8 | 80            | 1    |
| FIXED ARM 1 | ГҮРЕ                       |                         |            |        |               |      |
| MB/25F      | 45 × 48 × 50               | 1-3/4 × 1-7/8 × 2       | 200        | 8      | 40            | 4    |