

# 56

## Self Locking Pliers

SLP

Forged from Chrome Molybdenum Steel for higher strength & durability


Jaws are induction hardened 45-60 HRC for maximum torque with minimum input pressure

Curved jaw design grips nut and bolt head with high pressure on four points, which provides powerful tightening for applications requiring high torque

Spring loaded release mechanism provides controlled release making it ideal for applications in restricted space.

Wide adjustment screw coupled with rolled thread spindle provides for smoother adjustment of pressure on the work-piece

Non-pinch & rubberised non-slip grip for fatigue free use



### ORDERING INFORMATION

CAT NR.	LENGTH		BOX QTY.
	(INCH)	(MM)	
SLP/7C	7	175	5
*SLP/10C	10	250	5

\* Best Seller

# 57

## Adjustable Pipe Wrenches Stillson Pattern

SPW

Manufactured from selected tool steel


Accurately hardened & tempered jaws & frame

Jaws with Vee grooves to hold round jobs securely

Accurately machined screw threads and nut with spring jaws

### NOTE

These should not be used on nuts, bolts & hexagonal fittings where they could cause damage



For holding small & flat jobs conveniently

ACME threads for improved load bearing capacity

### ORDERING INFORMATION

CAT NR.	LENGTH		MAX. OPENING		BOX QTY.
	(INCH)	(MM)	(INCH)	(MM)	
*SPW/10	10	250	1-5/16	33	10
*SPW/12	12	300	1-21/32	42	10
SPW/14	14	350	1-7/8	48	10
SPW/18	18	450	2-3/8	60	8
SPW/24	24	600	2-7/8	73	5

\* Best Seller