

Tyre Inflator Gauge for Cars

TIG

Reliable and sturdy, the 3 in 1 GROZ tyre gauge is designed to:

- Measure Tyre Pressure
- 2. Inflate Tyres
- 3. Deflate Tyres

Tyre deflation is via the deflation valve on the gun body. A simple press of the valve will activate it and reduce pressure.

Available with choice of

- a. Analog Gaugeb. Digital Gauge

Aluminium die cast gun with flexible hose & straight chuck suitable for cars & other light vehicles

SPECIFICATION

| Gauge Type | Digital | Analog |
|----------------|-----------------------|-----------------------|
| Gauge Diameter | 2-1/2" (63 mm) | 2-1/2" (63 mm) |
| Backlight | Yes | - |
| | PSI, BAR, Mpa, Kg/cm2 | PSI, BAR |
| Max. Pressure | Upto 300 PSI (21 BAR) | upto 50 PSI (3.5 BAR) |
| Accuracy | ± 1% of Full scale | ± 1.6% of Full scale |
| Resolution | 0.1 PSI | 5 PSI |
| Power Supply | Lithium Battery | - |







Tyre Inflator with Digital Gauge



ORDERING INFORMATION

| CAT NR. | DESCRIPTION | BOX QTY. |
|--------------|---|----------|
| TIG/M/12/BSP | 12" (300 mm) flexible hose with straight chuck; Analog Gauge | 10 |
| TIG/D/12/BSP | 12" (300 mm) flexible hose with straight chuck; Digital Gauge | 10 |



Tyre Inflator Gauge for Trucks

Reliable and sturdy, the 3 in 1 GROZ tyre gauge is designed to:

- Measure Tyre Pressure
- Inflate Tyres
- Deflate Tyres

Tyre deflation is via the deflation valve on the gun body. Simple press of the valve activates it and reduces pressure

Available with choice of:

- a. Analog Gaugeb. Digital Gauge

Aluminium die cast gun with flexible hose, rigid extension & dual chuck suitable for attachment on valves of large tyres

SPECIFICATION

| Gauge Type | Digital | Analog |
|-----------------------------|-----------------------------|-----------------------|
| Gauge Diameter | 2-1/2" (63 mm) | 2-1/2" (63 mm) |
| Backlight | YES | - |
| Available Unit Selection | AR PSI, BAR, Mpa, Kg/cm2 | PSI, BAR |
| Max. Pressure | upto 300 PSI (21 BAR) | upto 50 PSI (3.5 BAR) |
| Accuracy | ± 1% of Full scale | ± 1.6% of Full scale |
| Resolution | 0.1 PSI | 5 PSI |
| Power Supply | Lithium Battery | - |

ORDERING INFORMATION


| CAT NR. | DESCRIPTION | BOX QTY. |
|---------------|---|----------|
| TIG/M/24D/BSP | 24" (600 mm) flexible hose with dual chuck; Analog Gauge | 10 |
| TIG/D/24D/BSP | 24" (600 mm) flexible hose with dual chuck; Digital Gauge | 10 |











MAINTAINING CORRECT TYRE PRESSURE

Under-inflated tyres heats up more quickly than correctly inflated tyres, and in extreme cases can lead to tyre failure

Driving on under-inflated tyres also places excess stress on the tyre shoulders, causing uneven wear of the tread

Over-inflation causes high wear at the centre of the tread

Correct tyre pressure ensures safety, optimum handling and longer life of the tyre